

# **DATASHEET**

# **Sheep Tag**

Tag Code: L441131

Sheep Tag is ICAR approved and ideal for identification, tracking and health and nutrition management. Sheep Tag is especially made using TPU material and over moulded to make it more robust and durable in outdoor environment. It is available in different animal modes including FDX as well as HDX.



### **Electrical Specification**

| Air Interface Protocol | ISO/IEC 11784/85, Animal mode: FDX, HDX  |
|------------------------|--|
| Operational Frequency  | 134.2KHz   |
| Chip**                 | EM4305 FDX   |
|                        | 512 bit EEPROM organized in 16 words of 32 bit   |
|                        | <ul> <li>32 bit unique identifier (UID)</li> <li>32 bit Password read and write protection</li> <li>Lock feature converts EEPROM words into Read Only</li> <li>Two data encodings: Manchester and Bi-phase</li> <li>Multi-purpose data rate: 8, 16, 32, 40 and 64 RF clocks</li> </ul> |

## **Physical / Mechanical Specification**

| Diameter          | Ø26 mm             |
|-------------------|--------------------|
| Height            | 13mm               |
| Weight            | 5.6gm              |
| Encasement        | TPU                |
| Color**           | Yellow             |
| Quality Assurance | 100% reader tested |

#### **Environmental Resistance**

| Operating temperature     | -40°C to +80°C                 |
|---------------------------|--------------------------------|
| Storage temperature       | -40°C to +80°C                 |
| Ingress protection rating | IP 67                          |
| Attachment***             | With Male Pin using Applicator |
| Expected Lifetime         | Years is normal operating      |
| LAPECIEU LIIEUIIIE        | conditions                     |



#### **Chemical Resistance**

Resistant to continuous exposure to salt water for 2 hours

Resistant to continuous exposure to motor oil for 2 hours

Additionally, abrasion resistant against HCL and IPA

#### **Additional Services**

| Pre-encoding     | On request                      |
|------------------|---------------------------------|
| Customization*** | Logo / text printing on request |

- Actual Read range may vary depending upon the reader and environmental factor
- \*\* Other on request
- \*\*\* Available as an option at extra cost

#### **Order Information**

| L44124A | With SIC 7999 HDX |
|---------|-------------------|
| L44129A | With SIC 7888 FDX |
| L441055 | With HitagS 256   |
| L441219 | With Hitag micro  |

