


UHF Aries Tag

Product Code: U7514122

The Aries tag is a medium-sized UHF Gen2 passive tag with a long range. It is suited for harsh environments and gives excellent performance on metallic and non-metallic things. It is available in three variants: on metal tag, off metal tag (free air), and all surface tag. Hence, it is a universal type of tag that may be used on any surface depending on the application.



Tag Dimensions



All dimension are in mm

Electrical Specifications


Air Interface Protocol	ISO/IEC 18000-63
Operational Frequency	860 – 960 MHz
Chip**	Impinj M730
Memory Configuration	EPC– Up to 128-bits
	TID – 96 bits of Serialized with 48-bit serial number
	User memory – Up to 64 bits
	Access password – 32 bits
	Kill password – 32 bits
Read Range*	Off metal: Up to 16 meters on Fixed reader
	On metal: Up to 8 meters on Fixed reader All surface: UP to 5 meters on Fixed reader
Operating Temperature	-40°C to +80°C
Storage Temperature	-40°C to +80°C
Ingress protection Rating	IP67
Attachment***	Self-Adhesive / Rivet
Applicable Surface	Metal / All Surface / Off Metal

Physical and Mechanical Specification

Dimensions	100 x 21 x 6 mm
Colour**	Grey
Weight	12 g
Encasement	ABS High Impact / PC
Quality Assurance	100 % Reader Tested
Chemical Resistance	

Resistant to continuous exposure to salt water for 2 hours	
Resistant to continuous exposure to motor oil for 2 hours	
Additionally, abrasion resistant against HCL and IPA	

Frequency v/s Read Range Graph



Additional Services

Pre-encoding	On request
Customization***	Logo / text printing on request

Order Information

U7514122M	With Impinj M730 (On metal)
U7514122O	With Impinj M730 (All Surface)
U7514122A	With Impinj M730 (Off metal)

*	Actual read range may vary depending upon the reader
**	Other on request
***	Available as an option at extra cost

