


UHF Label – 60 x 20 mm

Product Code: U9C34122

UHF polyester labels are versatile RFID labels engineered to provide efficient and accurate tracking and identification solutions for a wide range of industries and applications. These labels combine the benefits of UHF RFID technology with the convenience and cost-effectiveness of polyester-based labelling, making them an ideal choice for inventory management, asset tracking, logistics, and more.



Tag Dimensions



Label Information

Face Stock	Polyester
Adhesive	General based adhesive
Attachment***	Self-Adhesive
Applicable surface	Plastic, Wooden


Electrical Specifications

Air Interface Protocol	ISO/IEC 18000-6C, EPC Global C1G2
Operational Frequency	860 – 960 MHz
Chip**	Imping Monza 730
Memory Configuration	EPC Memory – 128-bits
	TID – 96 bits / 48-bit unique serial number
	User memory – N/A
	Access password – 32 bits
	Kill password – 32 bits
Data Retention	50 Years
Writ endurance	200,000 cycles
Read Range*	Up to 8 meters with the fixed reader with linear antenna
Operating temperature	-40°C to +85°C
Storage temperature	-40°C to +85°C


Physical and Mechanical Specification

Dimensions	60 ± 0.1 mm x 20 ± 0.1 mm
Delivery format	Reel
No. of labels per reel **	2000pcs/ reel
Quality Assurance	100% reader tested

Linear Frequency Graph



Orientation Sensitivity



All graphs are indicative: performance in real life applications may vary.

Additional Services

Customization***

Logo/text printing on request

- * Actual read range may vary depending upon the reader
- ** Other on request
- *** Available as an option at extra cost

Omnia Technologies Pvt. Ltd.

Plot No. 68, Sector-5, IMT Manesar, Gurugram, Haryana-122050, INDIA

Email: sales@omniatags.com